

ADVANTAGE DKS II



24-1000

MASTER CONTROLLERS FOR WIEGAND DEVICES

FEATURES

- 1,000 five-digit access-code capacity
- 26-bit Wiegand inputs
- Two relays with split-relay function
- "3 strikes, you're out" security
- Personal master code
- Latch code
- Sleep code
- True anti-passback
- Variable relay time
- Non-volatile memory
- Audible tones and LED feedback
- Nightlight (on post-mount model only)



EASY AND EXPANDABLE

Connect up to two Wiegand keypads for an easy-to-use, robust access control system.

ONE FOR EVERY NEED

Whether you're placing it in an office or mounting it outside on a pedestal or other location, we have a model for you.

STURDY & DURABLE

Crafted exclusively from stainless and powder-coated steel, these units will last!

PROGRAMMING YOU KNOW

Quick, simple, and familiar, the programming steps on the keypad are similar to those on other Security Brands, Inc. keypads.



SPECIFICATIONS

ELECTRICAL

Input	16.5 VAC 16.5-VAC transformer included
Current Draw	less than 40 mA @ 12 VDC less than 22 mA @ 24 VDC standby with nightlight less than 67 mA @ 12 VDC less than 35 mA @ 24 VDC with relay latched

RELAY

Contact Rating	1 A @ 24 V / .5 A @ 120 V DC Load / AC Load
Max Switching Voltage	150 V / 220 V
Max Carrying Current	2 A / 2 A
Max Switching Power	28 W / 60 VA
Variable Relay Time	1-999 seconds

ENVIRONMENTAL

Operating Temperature	-15 to 175 °F
-----------------------	---------------



24-1000

POST MOUNT*

5-1/4"(H) x 4-3/4"(W) x 4-1/2"(D)



24-1000d

DESK MOUNT

2-3/4"(H) x 5-3/4"(W) x 6-1/4"(D)

AVAILABLE MODELS

MODEL	DESCRIPTION	SHIPPING WT.
24-1000	post mount	6 lbs.
24-1000d	desk mount	5 lbs.
24-1000rt	raintight	9 lbs.
24-1000k	desktop kit	25 lbs.



24-1000rt

RAINTIGHT

8-1/4"(H) x 8-1/4"(W) x 4"(D)

* Only allows one dependent keypad to be connected.



1675 W Yale Ave
Englewood, CO 80110

Tel: (800) 541-5677
Fax: (303) 799-9756

securitybrandsinc.com