

CHARGERS



S-TC1A, S-TC36A

BATTERY TRICKLE CHARGERS

FEATURES

- Microprocessor-controlled
- LED indicators
- Overcharge protection
- Weather-resistant housing
- Ring terminal connections
- For use with 6 and 12-volt batteries*



* S-TC36A for use with 12-volt batteries only.

A SOLUTION FIT FOR YOU

From light-duty to robust, we have the charger for you, no matter the application.

NO MORE DEAD BATTERIES

Make dead batteries a thing of the past! Keep the batteries on everything from RVs to gate operators charged and ready to go.

RUGGED & DURABLE

With an IP65-rated, weather-resistant enclosure, our chargers are made to last!

INTELLIGENT CHARGING

By providing a charge only when needed, our chargers keep your battery charged safely with no risk of overcharge.

SPECIFICATIONS

**S-TC1A**

1-AMP TRICKLE CHARGER
(6 AND 12-VOLT BATTERIES)

PRODUCT

Dimensions 5.6"(L) x 2.3"(W) x 1.5"(H)
Shipping Weight 1 lb.

ELECTRICAL

Input 110–120 VAC
Output (selectable) 6 VDC or 12 VDC, 1 A
Charging Voltage
6-volt battery $7.2\text{ V} \pm .13\text{ V}$
12-volt battery $14.4\text{ V} \pm .25\text{ V}$
Efficiency >70%

ENVIRONMENTAL

Operating Temperature -4 to 122 °F

**S-TC36A**

3.6-AMP TRICKLE CHARGER
(12-VOLT BATTERIES)

PRODUCT

Dimensions 2.44"(H) x 2.44"(W) x 1.30"(D)
Shipping Weight 1.1 lbs.

ELECTRICAL

Input 110–120 VAC
Output 12 VDC, 3.6 A
Charging Voltage $14.4\text{ V} \pm .25\text{ V}$
Efficiency >75%

ENVIRONMENTAL

Operating Temperature -4 to 122 °F



SECURITY BRANDS INC.TM
your *partner* in access control

Security Brands, Inc.
1675 W Yale Ave
Englewood, CO 80110

Phone: (303) 799-9757
Toll-Free: (800) 541-5677
Fax: (303) 799-9756

securitybrandsinc.com