



14-500

433-MHZ KEYPAD AND TRANSCEIVER


FEATURES

- 500 four-digit access-code capacity
- · Latch mode
- · Wireless range up to 500 feet
- Control up to 2 devices from 1 keypad*
- Pair up to 40 keypads and/or remotes
- · Personal master code
- Limited-use code (1 to 9 uses)
- "3 strikes, you're out" security
- · Variable relay time
- Audible-tone and LED feedback
- · LED-backlit keypad
- Polycarbonate construction















GOES WHERE YOU GO

No wires mean freedom—this system can be located and mounted anywhere you need it.

FITS YOUR NEEDS

Whether it's a simple installation or a multiple-keypad/multiple-remote setup, your configuration options are limitless.

SOLAR FRIENDLY

An ultra-low current draw means it plays well with your solar gate operator.

GO WIRELESS

Ridge Wireless™ technology allows two-way wireless connection, making your system more versatile and more responsive.












SPECIFICATIONS (KEYPAD)

ELECTRICAL Input 9 VDC * ENVIRONMENTAL Operating Temperature -15 to 158 °F

SPECIFICATIONS (TRANSCEIVER)

ELECTRICAL Input 12-24 VAC/DC Current Draw less than 7.9 mA @ 12 VDC standby less than 11.2 mA @ 12 VDC with relay latched RELAY Contact Rating 2 A @ 30 V / .5 A @ 120 V DC Load / AC Load Max Carrying Current 2A/2A Variable Relay Time 1-999 seconds COMMUNICATION Radio Frequency 433 MHz **ENVIRONMENTAL** Operating Temperature -15 to 158 °F


MOUNTING (KEYPAD)



HOLE SIZES

Wiring pass through	0.88"
Mounting holes (x4)	0.38"

Unit includes mounting hardware.



14-500T keypad shown

AVAILABLE MODELS (See Price Guide to see all models, including Remote & Keypad HD)

MODEL	DESCRIPTION	DIMENSIONS	SHIP. WEIGHT
14-500	keypad and transceiver	see component dimensions	3 lbs.
14-500T	keypad	5.74"(H) x 4.87"(W) x 4.73"(D)	3 lbs.
14-REC20	transceiver	5.25"(H) x 2.75"(W) x 1.13"(D)	1 lb.

For more information, visit us online:

securitybrandsinc.com



^{*} Includes 9-V alkaline battery.